

# STLP-DC-14GA76

## Low Pass Filter

## Specifications

| S/N | Item                     | Parameters                                                                                    |
|-----|--------------------------|-----------------------------------------------------------------------------------------------|
| 1   | Cut Off Frequency        | 14GHz                                                                                         |
| 2   | Pass Band Frequency      | DC ~ 14GHz                                                                                    |
| 3   | Pass Band Insertion Loss | $\leq 1.0\text{dB @ DC} \sim 13.6\text{GHz}$<br>$\leq 2.0\text{dB @ } 13.6 \sim 14\text{GHz}$ |
| 4   | Pass Band VSWR           | $\leq 1.5:1$                                                                                  |
| 5   | Stop Band Attenuation    | $\geq 50\text{dB @ } 15.2 \sim 21.7\text{GHz}$                                                |
| 6   | Impedance                | 50 Ohms                                                                                       |
| 7   | Power Handling           | 15W Max.                                                                                      |
| 8   | Connectors               | SMA-Female                                                                                    |
| 9   | Surface Finish           | Painted Black                                                                                 |
| 10  | Temperature Range        | $-55^{\circ}\text{C} \sim +85^{\circ}\text{C}$                                                |
| 11  | Dimensions               | 22*17.5*10mm                                                                                  |
| 12  | Configuration            | As below (Tolerance: $\pm 0.3\text{mm}$ )                                                     |

