

## 60 to 220MHz – Drop in Isolator

### Design Features

- ◆ Can be dual junction even three for high isolation.
- ◆ Custom design available upon request.
- ◆ Military, space and commercial applications.
- ◆ Guaranteed for one year standard.

### RF Characteristics

Model Number	Freq. Range (MHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
TSDI6060A60T65	60 ~ 65	1.2	18	1.3	100	30	TAB	-10 ~ +65
TSDI6060A65T70	65 ~ 70	1.2	18	1.3	100	30	TAB	-10 ~ +65
TSDI6060A68T88	68 ~ 88	1.3	18	1.3	100	30	TAB	-20 ~ +65
TSDI6060A70T85	70 ~ 85	1.0	20	1.25	100	30	TAB	-20 ~ +65
TSDI6060A70T90	70 ~ 90	1.2	18	1.3	100	30	TAB	-20 ~ +65
TSDI6060A80T120	80 ~ 120	1.2	18	1.35	50	30	TAB	0 ~ +65
TSDI6060A85T135	85 ~ 135	1.2	18	1.3	80	30	TAB	-10 ~ +65
<b>TSDI6060A88T108</b>	<b>88 ~ 108</b>	<b>0.65</b>	<b>20</b>	<b>1.25</b>	<b>100</b>	<b>30</b>	<b>TAB</b>	<b>-20 ~ +65</b>
TSDI6060A88T138	88 ~ 138	1.0	18	1.3	80	30	TAB	-10 ~ +65
TSDI6060A100T130	100 ~ 130	0.7	18	1.3	100	30	TAB	-30 ~ +70
TSDI6060A100T130P200	100 ~ 130	0.7	18	1.3	200	30	TAB	-30 ~ +70
TSDI6060A100T150	100 ~ 150	1.0	18	1.3	80	30	TAB	-30 ~ +70
TSDI6060A108T118	108 ~ 118	0.6	23	1.2	100	30	TAB	-30 ~ +70
TSDI6060A108T118P200	108 ~ 118	0.6	23	1.2	200	30	TAB	-30 ~ +70
TSYDI6060A118T137	118 ~ 137	0.6	20	1.25	100	30	TAB	-30 ~ +70
TSDI6060A118T137P200	118 ~ 137	0.6	20	1.25	200	30	TAB	-30 ~ +70
TSDI6060A136T174	136 ~ 174	0.6	20	1.25	100	30	TAB	-30 ~ +70
TSDI6060A156T163	156 ~ 163	0.5	20	1.25	100	30	TAB	-30 ~ +70
TSDI6060A150T200	150 ~ 200	0.7	18	1.3	100	30	TAB	-30 ~ +70
TSDI6060A170T200P200	170 ~ 200	0.6	20	1.25	200	30	TAB	-30 ~ +70
TSDI6060A180T220	180 ~ 220	0.5	20	1.25	100	30	TAB	-30 ~ +70

- ◇ List are specify frequency range and other ranges available.
- ◇ Please enter below information when inquiry and mark \* is must.
  - \* 1. The specific frequency range
  - \* 2. Power handling (Forward, Reverse, Peak, etc.)
  - \* 3. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

### Mechanical Drawing

